

I claim:

- 1 1. A method of displaying an image, comprising:
 2 transmitting a first portion of first video image data to a first video memory in a
 3 first display device; and
 4 updating the first video memory with the first portion;
 5 wherein the first portion contains video data representing a part of the first video
 6 image data that has changed since a previous transmission to the first
 7 display device, and the first portion excludes a substantial part of the first
 8 video image data that is unchanged since the previous transmission to the
 9 first display device.
- 1 2. The method of claim 1, further comprising refreshing a first displayed image in
 2 the first display device from the first video memory.
- 1 3. The method of claim 1, wherein transmitting a first portion is repeated at regular
 2 intervals.
- 1 4. The method of claim 1, wherein transmitting a first portion is repeated at irregular
 2 intervals.
- 1 5. The method of claim 4, wherein said irregular intervals are based on detecting a
 2 change in the first video image data since a previous transmission to the first display
 3 device.

1 6. The method of claim 1, further comprising:
 2 transmitting a second portion of second video image data to a second video
 3 memory in a second display device; and
 4 updating the second video memory with the second portion;
 5 wherein the second portion contains video data representing a part of the second
 6 video image data that has changed since a previous transmission to the
 7 second display device, and the second portion excludes a substantial part
 8 of the second video image data that is unchanged since the previous
 9 transmission to the second video display device.

1 7. The method of claim 6, wherein the first portion and the second portion are
 2 transmitted over a same communications channel.

1 8. The method of claim 7, wherein the communications channel is a bus.

1 9. The method of claim 7, wherein the communications channel is a daisy chain
 2 cable.

1 10. The method of claim 7, wherein the first portion and the second portion are
 2 formatted differently.

1 11. The method of claim 7, wherein the first portion and the second portion are
 2 formatted alike.

1 12. The method of claim 7, wherein the first portion includes an address to identify
 2 the first video device and the second portion includes an address to identify the second
 3 video device.

SUBA4
cont

- 1 13. The method of claim 1, further comprising:
2 transmitting a second portion of data to the first display device;
3 time-stamping the first and second portions before transmission; and
4 synchronizing a presentation of the first and second portions based on the time-
5 stamping.

1 2 3 4 5 6 7 8

- 1 14. A display device, comprising:
2 a memory to store image data for display of a video image; and
3 a receiver to detect a predetermined device address in a received data stream
4 containing video data for updating a portion of the stored image data;
5 wherein the video data includes a part of the image data that has changed since a
6 previously received data stream, and the video data excludes a substantial
7 part of the image data that is unchanged since the previously received data
8 stream.

SUBA5

- 1 15. The display device of claim 14, further comprising a protocol handler to interpret
2 the received data stream.

- 1 16. The display device of claim 14, further comprising a timing generator to generate
2 timing signals for a display.

- 1 17. The display device of claim 16, further comprising a control circuit to configure
2 the timing generator.

- 1 18. The display device of claim 14, further comprising a scalar circuit to change a
2 granularity of the video image.

2

2

2

1

1

1

1 25. The system of claim 24, wherein a protocol of the first message is different than a
2 protocol of the second message.

26. The system of claim 24, further comprising a non-display device coupled to the communications channel to receive non-video data.